

- Large Current Capacity
- Low Collector–To–Emitter Saturation Voltage (Resistance) $R_{CE \, (sat)} \, typ. = 285 \, m\Omega \, [I_C = 1 \, A, I_B = 50 \, mA]$
- Small ON-Resistance (Ron)
- This Device is Pb-Free

Applications

 Low-Frequency Amplifier, High-Speed Switching, Small Motor Drive, Muting Circuit

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Conditions	Ratings	Unit
	-		_	
	-		-	
	-		_	
			_	

1

12A02MH

ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Conditions	Min	Тур	Max	Unit
	-	-	-	-	_	
	-	-	-	_	_	
				_		-
	-		-		_	
		-	-		_	
	-		-	-	_	
	1		-	-	_	
		– μ	_	_	_	
		- ∞	_	_	_	
		– μ	-	_	_	
	-		_		-	
			_		-	
			-		-	




Figure 1. Switching Time Test Circuit

12A02MH

TYPICAL CHARACTERISTICS




Figure 2. I_C - V_{CE}

Figure 3. I_C - V_{BE}






Figure 4. h_{FE} - I_C

V_{CE(sat),} Collector-to-Emitter Saturation Voltage (mV)





12A02MH

TYPICAL CHARACTERISTICS




Figure 9. C_{ob} – V_C






Figure 8. f_T - I_C


Figure 10. Ron – I_B

PACKAGE DIMENSIONS

-8







ons mi

