<u>Onsemi</u>,

• · · · · · • • • · · · ·

30 V, 300 mA, f_T = 3.5 GHz, NPN Single PCP

Features

- High f_T : ($f_T = 3.5$ GHz Typ)
- Large Current: $(I_C = 300 \text{ mA})$
- Large Allowable Collector Dissipation (1.3 W Max)
- These are Pb–Free Devices

Product & Package Information

- Package: PCP
- JEITA, JEDEC: SC-62, SOT-89, TO-243
- Minimum Packing Quantity: 1,000 Pcs./Reel

Specifications

ABSOLUTE MAXIMUM RATINGS (at Ta = 25° C)

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	V _{CBO}		40	V
Collector-to-Emitter Voltage	V _{CEO}		30	V

Emitter-to-Ba(Itage)O2 ref.1. re83o299 382. 0 8 280.6299 407.9055 Tm-.0174 Tc2 re83o299 382. 0 8 280.2 ref.1. re83o299 382. 0 8 280.6299 tter

ELECTRICAL CHARACTERISTICS



Land Pattern Example



SOT-89 / PCP-1 CASE 419AU ISSUE O

DATE 30 APR 2012

MECHANICAL CASE OUTLINE

0.

*

←

PACKAGE DIMENSIONS

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries. onsemi owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of onsemi's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. Onsemi reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and onsemi makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or incruit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using onsemi