


Is Now Part of



Application Diagram




Figure 1. Typical Application

Internal Block Diagram






Figure 2. Functional Block Diagram



Electrical Characteristics	FL6
V _{DD} =20 V and T _A =25°C unless otherwise specified.	FL6630 -
	ingle
)-Sta
	ige F
	rima
	ary-S
	ide-
	Regu
	latic
	n P
	M
	Single-Stage Primary-Side-Regulation PWM Controller for PFC and L
	rolle
	r for
	PFC
	and
	LEC
	LED Dimmable Driving
	ımal
	ole D
	rivir
	g
	ı

Floatrical Characteristics	⊒
Electrical Characteristics	FL6630
V _{DD} =15 V, T	30
	- 1
	Si
	<u>1</u>
	e-S
	itaç
	ge
	P
	ma
	Ž
	Sid
	e-F
	ζeç
	Jul 8
	tic
	ž
	Š
	S
	ğ
	 Single-Stage Primary-Side-Regulation PWM Controller for PFC and
	ĕ e
	ŕ
	ĭ
	Ĕ
	a
	Ε
	0
	LED Dimmable Driving
	ma
	ble
	Ō
	₹
	рg

Typical Performance Characteristics







Figure 5. V_{DD-ON} vs. Temperature

Figure 6. V_{DD-OFF} vs. Temperature







Figure 7. I_{DD-OP} vs. Temperature

Figure 8. V_{OVP} vs. Temperature






Figure 9. f_{MAX-CC} vs. Temperature

Figure 10. f_{MIN-CC} vs. Temperature

Typical Performance Characteristics	FL6630
	1.1
	- Sing
	gle-S
	tage
	Prim
	ary-
	Side-I
	Regu
	lation
	PW
	M Cc
	 Single-Stage Primary-Side-Regulation PWM Controller for PFC and
	ller fo
	or PF
	C and
	LED Dimmable Driving
	nmab
	le Dr
	iving

