

Is Now Part of


ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON




November 2014

## FSA550 4PST Depletion Mode Isolation Switch

Features			Description			
4PST (NC) Depletion Mo Audio Freque V <sub>CC(OFF)</sub> : 1.6 V R <sub>ON</sub> : 0.8 Ty R <sub>ON</sub> Flat: 0.01	ency Range / to 3.0 V /pical I Typica	) 		cc is present. This		
THD+N: 0.002% Typical Eco Status: Fairchild Green, RoHS Compliant, Halogen Free			feature is used to shift the electromagnetic interference (EMI) signature to meet customer specifications. <b>Related Resources</b>			
Applications	,		FSA550 Evaluation Board			
Cellular Phon	L_S R_S	Phones FSA55( SPKR SPKR SND Control IC Vcc Noise Cancelin IC	Gnd Gnd			
		Typic	al Application			
Ordering Info	ormatio		al Application			
Ordering Info Part Number	ormatio Top Mark		Package	Packing Method		
	Тор	n Operating				



addition, extended exposition addition addition addition at the second addition addition addition at the second addition additi	ended operating conditions and stressing the ure to stresses above the recommended opera gs are stress ratings only.	ating conditions may affec	t device r	eliability
Symbol	Parameter	Min.	Max.	Unit
		a <b>X 1</b> 844		



E	D	Х	Y
.16 mm	1.56 mm	0.18 mm	0.18 mm

BOTTOM VIEW

r L

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent\_Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductors are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized