



V_{CE}	Collector – Emitter Voltage	–	6	V
T_{OPR}	Operating Temperature	–40	+85	°C
T_{STG}	Storage Temperature	–40	+100	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Values are at $T_A = 25^\circ\text{C}$ and $V_{CE} = 5.0\text{ V}$, unless specified otherwise.



I_{L1}	Light Current 1	$E_V = 100\text{ lux (Note1)}$	7	10	–	μA
I_{L2}	Light Current 2	$E_V = 1000\text{ lux (Note1)}$	200	230	–	μA
I_{L3}	Light Current 3	$E_V = 1000\text{ lux (Note 2)}$	950	1100	–	μA

I_{L3} / I



CHIPLED ALS
CASE 100CP
ISSUE O

DATE 30 NOV 2016



.2

Collg

onsemi, **onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi**
