




NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. DAMBAR PROTRUSION SHALL BE 0.08 MAX. AT MMC. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT. MINIMUM SPACE BETWEEN PROTRUSION AND ADJACENT LEAD IS 0.07.
4. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.25 PER SIDE. DIMENSIONS D1 AND E1 ARE MAXIMUM PLASTIC BODY SIZE INCLUDING MOLD MISMATCH.
5. DIMENSIONS D2 AND E2 ARE MAXIMUM PLASTIC BODY SIZE INCLUDING MOLD MISMATCH. DIMENSIONS D3 AND E3 ARE MAXIMUM PLASTIC BODY SIZE BY AS MUCH AS 0.15.
6. DATUMS A-B AND D ARE DETERMINED AT DATUM PLANE H.
7. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.
8. DIMENSIONS D AND E TO BE DETERMINED AT DATUM PLANE C.




ALTERNATE CONSTRUCTIONAL TERMINOLOGY: DIMENSIONS D1 AND E1 ARE MAXIMUM PLASTIC BODY SIZE INCLUDING MOLD MISMATCH. DIMENSIONS D2 AND E2 ARE MAXIMUM PLASTIC BODY SIZE INCLUDING MOLD MISMATCH. DIMENSIONS D3 AND E3 ARE MAXIMUM PLASTIC BODY SIZE BY AS MUCH AS 0.15.



NOTE 7

32X



| DIM | MILLIMETERS | |
|-----|-------------|------|
| | MIN | MAX |
| A | --- | 1.20 |
| A1 | 0.00 | 0.15 |
| A2 | 0.95 | 1.05 |
| b | 0.15 | 0.27 |
| D | 7.00 BSC | |
| D1 | 5.00 BSC | |
| D2 | 3.40 REF | |
| D3 | 0.20 REF | |
| E | 7.00 BSC | |
| E1 | 5.00 BSC | |
| E2 | 3.40 REF | |
| E3 | --- | |
| e | 0.50 BSC | |
| L | 0.45 | 0.75 |
| L2 | 0.25 BSC | |
| M | 0 | 7 |