


WLCSP4, 0.96x0.96 CASE 567AW ISSUE O

DATE 26 JUL 2010




BOTTOM VIEW

NOTES: 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994. 2. CONTROLLING DIMENSION: MILLIMETERS. 3. COPLANARITY APPLIES TO SPHERICAL CROWNS OF SOLDER BALLS.

(CROWNS OF SOLDER B				
		MILLIMETERS			
	DIM	MIN	MAX		
	Α	0.56	0.72		
	A1	0.21	0.27		
	A2	0.42 REF			
	b	0.29	0.35		
	D	0.96 BSC			
	Е	0.96	BSC		
	e	0.50	BSC		

RECOMMENDED SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb–Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON49806E	Electronic versions are uncontrolled except when			
DESCRIPTION:					
onsemi and are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.					

SCALE 4:1