



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: MILLIMETER.
  3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
  4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
  5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.13 (0.005) TOTAL IN EXCESS OF D DIMENSION AT MAXIMUM MATERIAL CONDITION.

<b>B</b>	7.40	7.60	0.292	0.299
<b>C</b>	2.35	2.65	0.093	0.104
<b>D</b>	0.35	0.49	0.014	0.019
<b>F</b>	0.50	0.90	0.020	0.035
<b>G</b>	1.27 BSC		0.050 BSC	
<b>J</b>	0.25	0.32	0.010	0.012
<b>K</b>	0.10	0.25	0.004	0.009
<b>M</b>	0°	7°	0°	7°
<b>P</b>	10.05	10.55	0.395	0.415
<b>R</b>	0.25	0.75	0.010	0.029
<b>S</b>	2.54 BSC		0.100 BSC	
<b>T</b>	3.81 BSC		0.150 BSC	