




SSOP24 NB EP
CASE 940AP
ISSUE O

DATE 05 MAR 2015

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. DAMBAR PROTRUSION SHALL BE 0.10 MAX. AT MMC. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT. DIMENSION b APPLIES TO THE FLAT SECTION OF THE LEAD BETWEEN 0.10 TO 0.25 FROM THE LEAD TIP.
4. DIMENSION D DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. OT INCLUDE4JTJ1.4362 2C.7N6



M	0.15	C	A-B	D
------------	------	---	-----	---

NOTE 8
D2

C			
------------	--	--	--

E2
 NOTE 8

MILLIMETERS		
DIM	MIN	MAX
A		1.75
A1	0.00	0.10

b	0.19	0.30
c	0.09	0.20

D2	2.37	2.67
----	------	------

E2	1.79	1.99
e	0.65 BSC	
h	0.25	0.50
L	0.40	0.85
L1	1.00 REF	
L2	0.25 BSC	
M	0°	8°

BOTTOM VIEW

